

**ABSTRACT**

A terminal for generating an electromagnetic field adapted to communicating with at least one transponder, and a method for controlling such a terminal including: an oscillating circuit adapted to being excited by a remote supply signal of the transponder; an amplitude  
5 demodulator for detecting possible data transmitted by the transponder; circuitry for regulating the signal phase in the terminal's oscillating circuit on a reference value; circuitry for measuring variables linked to the current in the oscillating circuit and to the voltage thereacross; and circuitry for comparing current values of these variables to predetermined values, to determine the presence of a transponder.

(11)  
(12)  
(13)  
(14)  
(15)  
(16)  
(17)  
(18)  
(19)  
(20)  
(21)  
(22)  
(23)  
(24)  
(25)  
(26)  
(27)  
(28)  
(29)  
(30)  
(31)  
(32)  
(33)  
(34)  
(35)  
(36)  
(37)  
(38)  
(39)  
(40)  
(41)  
(42)  
(43)  
(44)  
(45)  
(46)  
(47)  
(48)  
(49)  
(50)  
(51)  
(52)  
(53)  
(54)  
(55)  
(56)  
(57)  
(58)  
(59)  
(60)  
(61)  
(62)  
(63)  
(64)  
(65)  
(66)  
(67)  
(68)  
(69)  
(70)  
(71)  
(72)  
(73)  
(74)  
(75)  
(76)  
(77)  
(78)  
(79)  
(80)  
(81)  
(82)  
(83)  
(84)  
(85)  
(86)  
(87)  
(88)  
(89)  
(90)  
(91)  
(92)  
(93)  
(94)  
(95)  
(96)  
(97)  
(98)  
(99)  
(100)